



FERMOSTOCK®

6611/R

Modular shelving system
with removable shelf inserts

No.1 in
EUROPE



- ✓ Quick assembly
- ✓ Easy to clean
- ✓ Lifetime warranty against corrosion



Maximum weight
loading 800 lbs / level *

* Further details inside

Storage system for clean environment



Cold rooms



Catering



Laundries



Laboratories



Stores



Clean rooms



Restaurants



Universities



Hospitals


Universal System





Tool-free Assembly



**Stabilization
via adjustable
composite feet**



Angle section



FERMOSTOCK leads the market in product layout and design, storage optimization, and hygiene awareness.

Offers completely flexible solutions for your storage needs.

Through its operating temperature range of - 40°F to 140°F (- 40°C to 60°C), Fermostock is the perfect solution for coldroom applications.

Extremely safe and reliable ; manufactured from high-strength aluminium, anodized to 20 microns.

Fermostock eliminates any need for cross-bracing and offers full access through its uniquely designed internal angle configuration system.

Shelf adjustment is quick and simple with preset positions 6 inches (150 mm) apart, allowing for individual adaptation to suit storage requirements.

Removable shelf inserts are manufactured of heavy-duty polymer and are dishwasher safe.

Design

Fermostock offers outstanding solutions in space management; ensuring maximum use of available storage area through different combinations of its standard units.

Fermostock offers efficient and cost-effective storage even within obstructed areas.

In addition to our in-house design service, we offer the ability of self-design through our Fermostock layout software.

Our commercial department is available to assist you with selection and layout services for all your projects.



Please find our calculation software for Fermostock shelving system online: www.fermostock.com



Solutions

Static modular shelving system

Assembly is through conical metal clamps manufactured of anodized aluminium ensuring extremely stable units. Fermostock can be installed in singular units or combinations allowing a number of configurations including « L », « U », « T », and « + », layouts.

Available standard sizes:

- **2 heights of uprights:**
71, 83 in.*
(1800, 2100 mm)
- **3 depths:**
14, 18, 22 in.*
(360, 460, 560 mm)
- **10 lengths:**
26, 31, 35, 38, 42, 47, 52, 59, 64, 68 in.*
(660, 780, 900, 960, 1080, 1200, 1320, 1500, 1620, 1740 mm).

* All dimensions in inches have been rounded



	Depths			Heights	
in.*	14	18	22	71	83
mm	360	460	560	1800	2100

Loading per Shelf Level (for evenly distributed load)										
Bay Length (in.*)	26	31	35	38	42	47	52	59	64	68
mm	660	780	900	960	1080	1200	1320	1500	1620	1740
Fermostock 6611/R (lbs)	800	800	800	800	800	800	600	600	600	600

Maximum weight is 2000 lbs between 2 uprights / 1300 lbs between 2 uprights with angle configuration

* All dimensions in inches have been rounded

Mobile Units

Mobile units are designed to be moved with a minimum of effort and to allow for full access when cleaning.

The castors are rustproof and made of high-quality polymer and stainless steel allowing for smooth operation.

Mobile units offer extra flexibility and increased storage capacity.

■ Construct with 3,4,5 levels or greater depending on requirements.




	Depths			Height
in.*	14	18	22	71
mm	360	460	560	1792

Loading per Shelf Level (for evenly distributed load)										
Bay Length (in.*)	26	31	35	38	42	47	52	59	64	68
mm	660	780	900	960	1080	1200	1320	1500	1620	1740
Fermostock 6611/R (lbs)	250	250	250	250	250	250	250	250	250	250

Please note maximum weight of 500 lbs between 2 uprights - * All dimensions in inches have been rounded

DUNNAGE RACKS

Manufactured with a standard height of 12 inches (300 mm), dunnage racks provide yet another range of applications. They can complete shelving systems within cold rooms, be placed under tables, be used for items suitable for only low-level storage, and for machines and other individual applications.



	Height
in.*	12
mm	300

	Depths		
in.*	14	18	22
mm	360	460	560

Loading per Shelf Level (for evenly distributed load)							
Bay Length (in.*)	26	31	35	38	42	47	52
mm	660	780	900	960	1080	1200	1320
Fermostock 6611/R (lbs)	800	800	800	800	800	800	600

* All dimensions in inches have been rounded

Installation

All Fermostock components are packaged and shrink-wrapped ensuring full protection during delivery and storage.

Assembly via the use of conical metal support clamps (patented) allows one person to carry out the installation quickly and efficiently without the need of tools.

Quick assembly and mounting:

- Choose shelf levels from the 11 or 13 preset positions on the upright (according to height),
- Insert the metal support clamp at the desired height,
- Position the horizontal shelf rails onto the metal clamps,
- Place the shelf inserts onto the horizontal rails,
- Adjust the composite feet to ensure stabilization.

Where angle-mounting, the use of the Fermostock angle section is recommended which eliminates internal corner posts and improves access.

& Compatibility

The benefits of Fermostock modular shelving systems

Fitters & technical engineering offices

FERMOD has been manufacturing, developing, and selling modular shelving systems for over thirty years .

FERMOSTOCK is accepted and designed for the food industry and recommended by engineers because of its quality, benefits, and easy installation.

The quality of our product is backed by a LIFETIME WARRANTY AGAINST CORROSION.

Our commercial and technical departments are always ready to assist and aid you with your shelving needs.

The product is dispatched to individual customers' requirements ensuring correct marking and wrapping to the final destination.

From their conception, our products are developed to help protect our environment. This result is achieved by producing durable items, using only the amount of raw material necessary and selecting recyclable material whenever possible. Our product is green and 100% recyclable to ensure environmental friendliness.


For end-users

All Fermostock surfaces are smooth, allowing for easy cleaning, and designed to withstand intensive and frequent cleaning activity to aid in the reduction of bacterial contamination. Fermostock modular shelving system is compatible with HACCP cleaning programs.

Certifying organizations

NSF International.

■ Polymer inserts are dishwasher safe (+ 212°F / +100°C)



FERMOSTOCK®



FERMOD®



500 Lake Cook Road - Suite 350 - Deerfield, IL 60015

Office: 847-231-0367 - Toll free: 888-484-0367

Fax: 847-231-0366

Email: uscontact@fermod.com

DEALER