



Project: _____

Location: _____

Item #: _____ Quantity: _____

Model #: _____

MODEL: **AGN 600 CR****REACH-IN:**
Slimline Reach-in Refrigerators (Glass Door)

AGN 600 CR

General Strengths

- ✓ **Sanitation.** The interior cabinet is built with rounded corners (extensive radius for easy cleaning). Quick ability to take off shelves and slides for interior cleaning. Each cabinet has a drain at the bottom of the unit. When cleaning the unit make sure the drain hose is routed to a floor drain.
- ✓ **Doors & Drawers.** Self-closing door system with permanent pressure. Stay open feature included when door remains open after 95 degrees. All doors and drawers include triple chamber door gaskets, easy to remove and snap in. Doors are field reversible.
- ✓ **Control systems.** Higher precision in managing temperature settings. Greater ability for the adjustment of temperatures ranges as per the end user's requirement.
- ✓ **100% Tested.** All condenser units are tested 100%, in helium chambers to refrigerant leak detections.
- ✓ **Certified.** Audited and Certified by **INTERTEK** for compliance with UL 471 and NSF 7. AENOR audited and certified by internationally recognized firm. ISO 9001:2008 (Quality); ISO 14001:2004 (Environmental); OSHAS 18001:2007 (Prevention and Worker Safety)
- ✓ **Lighting.** LED lighting in the canopy and cabinet sides reduces the energy consumption by 80% and 90% compared to a traditional bulb. Provides a much better light quality.

MODEL	Dimensions (inches) (mm)			N° Doors	N° Shelves	Ref.	Ref. Weight (Lbs.) (gr.)	Temp. Range (°F) (°C)	Capacity (Cu. Ft.) (L)	Cond. Unit. H.P.	Case Amps 115 V.	Crated Weight (Lbs.) (Kg.)
	W	D	H									
AGN 600 CR	38-3/8 975	27-3/8 695	83 2100	2	8	R134a	0.62 280	33°F/38°F 0°C/4°C	27 765	3/8	7.4	414 188

ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 - WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE

AUTODESK
REVIT

Infrico USA Corp.
3325 N.W. 70th Avenue
Miami, FL 33122-1332
1.305.777.9599 Office
1.305.777.9598 Fax

www.infrico.us
operations@infrico.com
service@infrico.com
sales@infrico.com

APPROVALS: AVAILABLE AT: _____



Project: _____
Location: _____
Item #: _____ Quantity: _____
Model #: _____

MODEL: **AGN 600 CR**

REACH-IN:
Slimline Reach-in Refrigerators (Glass Door)

STANDARD FEATURES

- **Exterior**

 - AISI 304 Stainless Steel.
 - Completely injected compact structure.

➤ **Interior**

 - AISI 304 Stainless Steel.
 - Wide rounded corners to aid cleaning.
 - LED lighting.
 - Internal drain.

➤ **Insulation**

 - High density CFC free Polyurethane foam.

➤ **Doors**

 - Self closing with stay open feature.
 - Integrated door handles.
 - AISI 430 Stainless Steel covered hinges.
 - Triple chamber snap in door seals for easy removal.
 - Thermopane double glass.
 - Door lock provided.
 - Full-height door opening: 14-3/4"x58-7/8" (375x1500 mm).
- **Shelving**

 - (4) Plastic-coated extra-dense wire shelves per door.
 - Set of Stainless Steel rails per shelf included.
 - Dimensions WxD: 12-3/4"x20-7/8" (324x530 mm).
 - Compatible with 12"x20" (305x500 mm). sheet pans.

➤ **Casters**

 - 4" diameter casters.
 - Locks provided on front set.

➤ **Refrigeration**

 - Temperature and defrost regulated by a digital controller.
 - Evaporative pan.
 - Evaporator coil coated with anti-corrosion material.



➤ **Electrical**

 - Cord and NEMA 5-15P plug.
 - Electrical connection is 115V / 1ph / 60 Hz.



OPTIONAL FEATURES

- ✓ Stainless Steel wire shelf.
- ✓ Set of 6" legs, height adjustable from 5" to 8".
- ✓ Electrical connection is 230V / 1ph / 50 Hz (plug type varies).



ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 - WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE