



Project: \_\_\_\_\_

Location: \_\_\_\_\_

Item #: \_\_\_\_\_ Quantity: \_\_\_\_\_

Model #: \_\_\_\_\_

MODEL: **EVV 23 RETRO****RETRO REFRIGERATORS / CONFECTIONERY**

### General Strengths

- ✓ **Sanitation.** The interior cabinet is built with rounded corners (extensive radius for easy cleaning). Quick ability to take off shelves and slides for interior cleaning. Each cabinet has a drain at the bottom of the unit. When cleaning the unit make sure the drain hose is routed to a floor drain.
- ✓ **Doors.** Self-closing door system with permanent pressure. Stay open feature included when door remains open after 95 degrees. All doors include triple chamber door gaskets, easy to remove and snap in.
- ✓ **Control systems.** Higher precision in managing temperature settings. Greater ability to adjust temperature ranges as per the end user's requirement.
- ✓ **100% Tested.** All condenser units are tested 100%, in helium chambers to refrigerant leak detections.
- ✓ **Certified.** Audited and Certified by **INTERTEK** for compliance with UL 471 and NSF 7. AENOR audited and certified by internationally recognized firm. ISO 9001:2008 (Quality); ISO 14001:2004 (Environmental); OSHAS 18001:2007 (Prevention and Worker Safety)
- ✓ **Lighting.** Interior cabinet includes LED lighting, for brighter lighting and energy efficiency. LED saves 90% more energy compared to traditional fluorescent bulbs. Increases product visibility considerably.

| MODEL           | Dimensions<br>(inches) (mm) |               |                | N°<br>Doors | N°<br>Shelves | Ref.  | Ref.<br>Weight<br>(Lbs.) (gr.) | Temp.<br>Range<br>(°F) (°C) | Capacity<br>(Cu. Ft.)<br>(L) | Cond.<br>Unit.<br>H.P. | Case<br>Amps<br>115 V. | Crated<br>Weight<br>(Lbs.)<br>(Kg.) |
|-----------------|-----------------------------|---------------|----------------|-------------|---------------|-------|--------------------------------|-----------------------------|------------------------------|------------------------|------------------------|-------------------------------------|
|                 | W                           | D             | H              |             |               |       |                                |                             |                              |                        |                        |                                     |
| EVV 23<br>RETRO | 30<br>760                   | 25-3/8<br>643 | 78-3/4<br>2000 | 1           | 7             | R134a | 0.59<br>270                    | 36°F/43°F<br>+2°C/+8°C      | 19.1<br>540                  | 1/3                    | 5.0                    | 265<br>120                          |

ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 - WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE

AUTODESK  
REVIT

**Infrico USA Corp.**  
3325 N.W. 70th Avenue  
Miami, FL 33122-1332  
1.305.777.9599 Office  
1.305.777.9598 Fax

**www.infrico.us**  
operations@infrico.com  
service@infrico.com  
sales@infrico.com

APPROVALS: AVAILABLE AT: \_\_\_\_\_



Project: \_\_\_\_\_

Location: \_\_\_\_\_

Item #: \_\_\_\_\_ Quantity: \_\_\_\_\_

Model #: \_\_\_\_\_

**MODEL: EVV 23 RETRO****RETRO REFRIGERATORS / CONFECTIONERY****STANDARD FEATURES**

- Refrigerated cupboards Retro model, manufactured for exhibiting, maintaining and preserving food products, catering and winery, with a design that resembles the type of furniture manufactured in the 1960's and built with the current production technologies.
- Usefulness (Utility): nourishment, hotel and catering business (hotel industry), restoration and warehouses.
- **Exterior**
  - Exterior of clump pine wood, back of galvanized metal plate with white surface painted 25μ and quality for a perfect hygiene.
- **Interior**
  - AISI 304 Stainless Steel.
  - Wide rounded corners to aid cleaning.
  - Panels sandwich type with thickness of 3-1/8" (80 mm) insulation.
  - LED lighting.
- **Insulation**
  - High density CFC free Polyurethane foam.
- **Shelving**
  - (7) Interior shelves per door.
  - Slides and shelves easy to take off for cleaning.
  - Dimensions WxD: 15-3/4"x22-1/4" (400x565) (mm).
- **Doors**
  - Glass doors with solid wood (treated and painted), a triple chamber door seal easy to change and double glass and illuminated positive temperatures.
  - The steel storm doors are inlaid to enlarge the thickness of the insulating of the door, a triple chamber door seal easy to change.
  - Zamak 5 chrome plated Hinge and Latch,
  - Full-height door opening: 19-5/8"x56" (500x1420) (mm).
- **Refrigeration**
  - Temperature and defrost regulated by a digital controller.
  - System of ventilated condensation IMPABLOCK®.
  - Forced air cooling.
  - Evaporator coil coated with anti-corrosion material.
  - Automatic evaporation of the water of the evaporating one.
- **Electrical**
  - Cord and NEMA 5-15P plug.
  - Electrical connection is 115V / 1ph / 60 Hz.

**PLAN VIEW****OPTIONAL FEATURES**

- ✓ Electrical connection is 220-230 V / 1ph / 50 Hz (plug type varies).

ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 - WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE

AUTODESK  
REVIT

**Infrico USA Corp.**  
 3325 N.W. 70th Avenue  
 Miami, FL 33122-1332  
 1.305.777.9599 Office  
 1.305.777.9598 Fax

**www.infrico.us**  
 operations@infrico.com  
 service@infrico.com  
 sales@infrico.com

**APPROVALS: AVAILABLE AT:**