

NOR-LAKE, INCORPORATED
727 Second Street
Hudson, Wisconsin 54016

800-955-5253
715-386-2323
866-961-5253 Parts
800-388-5253 Service
715-386-4291 FAX
www.norlake.com



ADVANTEDGE™ SLIDE GLASS DOOR REFRIGERATOR MERCHANDISERS



NLGRP48-SL



NLGRP74-SL

PROJECT:

ITEM NUMBER:

MODEL NUMBER:

SLIDE GLASS DOOR MERCHANDISERS

SPECIFICATIONS FOR: NLGRP48-SL, NLGRP74-SL

- **Finish:** 24 gauge painted textured galvanized steel interior and exterior. Black or white exterior finish. Standard white interior finish with stainless steel floor
- **Insulation:** 1-3/4" thick state-of-the-art, foamed-in-place "zero ODP" polyurethane insulation
- **Hardware:** Interior LED lighting with switch, interior hanging thermometer, top backlit graphic panel (standard panel is blank without graphics), adjustable legs for leveling, four adjustable heavy-duty epoxy coated shelves per door - adjustable in 1/2" increments on pilasters
- **Doors:** Auto-close, triple pane, safety glass doors, contemporary style black door frame with anti-microbial handles. On NLGRP74 models, left door slides to middle, middle and right door slide to left.
- **Electrical:** 115 volt, 60 Hz, 1 phase with cord and plug
- **Refrigeration** Self-contained bottom mount refrigeration system designed for optimum energy efficiency and low noise. Top mounted, low profile interior evaporator housing for increased storage space, energy-free condensate removal. Refrigeration system is accessible for ease of service and regular preventative maintenance. Refrigerant: R-134a. Temperature range: +34° to +41°F. Electronic temperature control.
- **Approvals:** UL/C-UL Safety, UL Sanitation, and NRCan listed **

STANDARD FEATURES

- 24 gauge painted textured galvanized steel interior and exterior
- 2-1/2" adjustable legs for leveling
- Anti-microbial finish on door handles
- Auto-close, triple pane, safety glass doors
- Contemporary style black door frame
- Energy-free condensate removal
- Four adjustable heavy-duty epoxy coated shelves per door
- Interior hanging thermometer
- Interior LED lighting with light switch
- Refrigerant: R-134a
- Self-contained bottom mount refrigeration system
- Top backlit graphic panel (standard panel is blank without graphics)
- Temperature range: +34° to +41°F
- Top mounted, low profile interior evaporator housing for increased storage space
- White interior finish with stainless steel floor
- Warranties: 3 year parts and labor, 5 year compressor
- Approvals: UL/C-UL Safety, UL Sanitation, and NRCan

OPTIONAL FEATURES*

- Additional shelving
- Black or white exterior finish
- Casters
- Graphic sign panels
- Price tag molding for shelving



Nor-Lake, Inc.
Registered to ISO 9001:2008
File No. 10001816

* Most options are available two weeks from receipt of order. Please contact us for specific questions.

** C-UL is Underwriters Laboratories Safety Certification Mark which indicates that UL has tested the equipment to applicable CSA Standards.

** UL Sanitation is Underwriters Laboratories Sanitation Mark which indicates that UL has tested the equipment to applicable NSF Standards.

Technical drawing of the front view of the cabinet. The main body dimensions are: total width 30", total height 79", and depth 12-1/2". The glass door dimensions are: width 28", height 65-1/2", and depth 12-1/2". The door is divided into three horizontal sections: a top section with a height of 8-1/4", a middle section with a height of 57-1/4", and a bottom section with a height of 54-1/2". The middle section contains three horizontal bars, with a spacing of 21-1/2" between them. The top section contains a single horizontal bar, and the bottom section contains a single horizontal bar. The door is shown slightly ajar, revealing the interior shelves.

Diagram illustrating the dimensions and components of the NLGRP74-SL sign structure:

- Overall width: 78" - NLGRP74-SL
- Overall height: 79"
- Top section: LIGHTED SIGN
- Two vertical glass doors, each labeled GLASS DOOR.
- Bottom section: Four horizontal slats.

		SPECIFICATIONS	
Models	NLGRP48-SL	NLGRP74-SL	
Crated Weight (lbs) (kg)	530 (239)	715 (322)	
Crated Height (in) (cm)	86 (215)	86 (215)	
Crated Width (in) (cm)	60 (150)	88 (220)	
Crated Depth (in) (cm)	42 (105)	42 (105)	
Interior Height (in) (cm)	54-1/2 (138)	54-1/2 (138)	
Interior Width (in) (cm)	48-1/2 (123)	74-1/2 (189)	
Interior Depth (in) (cm)	24-1/2 (62)	24-1/2 (62)	
Overall Height (in) (cm)	79 (201)	79 (201)	
Overall Width (in) (cm)	52 (132)	78 (198)	
Overall Depth (in) (cm)	30 (76)	30 (76)	
Gross Cubage (ft³) (L)	45.7 (1293)	70.2 (1987)	
Number of Shelves	8	12	
Shelf Size (in)	23-1/2 x 21-1/2	23-1/2 x 21-1/2 (outer doors) 25-1/2 x 21-1/2 (middle door)	
Condensing Unit Size	1/3 HP	1/2 HP	
Refrigerant	R-134a	R-134a	
Electrical Characteristics	115/60/1	115/60/1	
Cord and Plug Furnished	Yes	Yes	
Maximum Fuse Size	15 Amps	15 Amps	
Nema Plug Configuration	5-20P	5-20P	
Total Amp Draw	6.9	7.7	



Revision Date: 03/17
© 2013 NOR-LAKE, INC.
Printed in the U.S.A.
Part Number: 152102